Data sheet



Part No. CB 2-U WH

Description

through box

Circular box for surface installation with 2 mounting lugs, standard mounting screw spacing 50.8mm (2") for conduit diameters 20mm to 25mm, with brass inserts M 4, without lid

Colour


white, similar to RAL 9010



Standard: BS 4607, EN 60670

CECA

Working temperature	Degree of protection (IP)	Number of inlets	Material	
-5 to +60 °C	IP3X	2	PVC-U	
Art. no.	Dimensions Ø/LxW x D	For tube diameter	ps	pl
009 373 CB 20/2-U WH	65 x 32 mm	20 mm	20 pc	160 pc
009 375 CB 25/2-U WH	65 x 32 mm	25 mm	20 pc	160 pc



All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice. Fully responsible for the content: UNIVOLT (UK) Ltd. Unit 4, Quadrant Park, Black Fan Road, Welwyn Garden City AL7 1FS.