

Data sheet

Part No.	MAK WH
Description	maxi trunking Cable routing system for all kinds of electrical installations and telecommunication systems (telephone, EDP, TV, IT etc.) in residential and industrial buildings, offices, garages, hotels, schools and kindergartens; special clip-on system for robust connections between trunking body and lid (shock- and child-proof).
Colour	white, similar to RAL 9010
Fire Behaviour	non flame propagating



Standard: EN 50085, BS 4678 Part 4



Length	Working temperature	Material
3000 mm	-25 to +60 °C	PVC-U

Art. no.	Width x Depth	ps	pl
036 996 MAK 50/50 WH 3M	50 x 50 mm	3 m	12 m
019 007 MAK 50/75 WH 3M	75 x 50 mm	3 m	12 m
036 997 MAK 50/100 WH 3M	100 x 50 mm	3 m	12 m
022 788 MAK 50/150 WH 3M	150 x 50 mm	3 m	6 m
019 008 MAK 75/75 WH 3M	75 x 75 mm	3 m	12 m
019 010 MAK 75/100 WH 3M	100 x 75 mm	3 m	6 m
022 953 MAK 75/150 WH 3M	150 x 75 mm	3 m	6 m
019 011 MAK 100/100 WH 3M	100 x 100 mm	3 m	6 m
022 789 MAK 100/150 WH 3M	150 x 100 mm	3 m	84 m
022 790 MAK 150/150 WH 3M	150 x 150 mm	3 m	60 m

